

PART B — (5 × 16 = 80 marks)

11. (a) (i) Air flows down a variable area duct. Measurements indicate that the temperature is 278 K and the velocity is 150 m/s at a certain section of the duct. Measurements at a second section indicate that the temperature has decreased to 253 K. Assuming that the flow is adiabatic and one dimensional, find the velocity at this second section. (6)

- (ii) Typical cruising speeds and altitudes for three commercial aircraft are:

Dash 8: Cruising speed- 500 km/hr at an altitude of 4500m.

Boeing 747: Cruising speed: 978 km/hr at an altitude of 9500 m

Find the Mach number of the aircraft when flying at these cruise conditions. (10)

Or

- (b) Air flows through a nozzle which has inlet areas of 0.001 m^2 . If the air has a velocity of 80 m/s, a temperature of 301 K and a pressure of 700 kPa at the inlet section and a pressure of 250 kPa at the exit, find the mass flow rate through the nozzle and assuming one-dimensional isentropic flow, the velocity at the exit section of the nozzle. (16)

12. (a) Air flows out of a pipe with a diameter of 0.3 m at a rate of $1000 \text{ m}^3/\text{min}$ at a pressure and temperature of 150 kPa and 293 K respectively. If the pipe is 50m long, find assuming that $f = 0.005$, the Mach number at the exit, the inlet pressure and the inlet temperature. (16)

Or

- (b) The condition of a gas in a combustor at entry is: $p_1 = 0.343 \text{ bar}$, $T_1 = 310 \text{ K}$, $c_1 = 60 \text{ m/sec}$. Determine the Mach number, pressure, temperature and velocity at the exit if the increase in stagnation enthalpy of the gas between entry and exit is 1172.5 kJ/kg . Take $c_p = 1.005 \text{ kJ/kg K}$, $\gamma = 1.4$. (16)

13. (a) A normal shock occurs in the diverging section of a convergent - divergent air nozzle. The throat area is $1/3$ times exit area and the static pressure at exit is 0.4 times the stagnation pressure at the entry. The flow is throughout isentropic except through the shock. Determine:

(i) Mach numbers M_x and M_y

(ii) The static pressure and

(iii) The area of cross section of the nozzle at the section of nozzle where the normal shock occurs. (16)

Or

- (b) A gas ($\gamma = 1.3$) at $p_1 = 345$ mbar, $T_1 = 350$ K and $M_1 = 1.5$ is to be isentropically expanded to 138 mbar.

Determine

- (i) the deflection angle
- (ii) final Mach number
- (iii) the temperature of the gas.

14. (a) Derive the following relations for aircraft engine

(i) Flight to jet speed ratio $\sigma = 1 - \frac{F}{\dot{m}_a c_j}$ (6)

- (ii) Thrust in a turbojet engine

$$F = \dot{m}_a(c_j - u) = \dot{m}_a(c_e - u) + (p_e - p_a)A_e \quad (10)$$

Or

- (b) An aircraft flies at 90 km/hr. One of its turbojet engines takes in 40 kg/s of air and expands the gases to the ambient pressure. The air-fuel ratio is 50 and the lower calorific value of the fuel is 43 MJ/kg. For maximum thrust power determine:

- (i) jet velocity
- (ii) thrust
- (iii) specific thrust
- (iv) thrust power
- (v) propulsive, thermal and overall efficiencies.

15. (a) Explain the working principle of a Turbo-pump feed system with a schematic diagram for liquid propellant rocket engines.

Or

- (b) Describe briefly the important applications of rocket propulsion in the following fields

- (i) Aircrafts
- (ii) Military
- (iii) Space
- (iv) scientific.