

11. (a) A nozzle in a wind tunnel gives a test-section Mach number of 2.0. Air enters the nozzle from a large reservoir at 0.69 bar and 310 K. The cross-sectional area of the throat is 1000 cm². Determine the following quantities for the tunnel for one dimensional isentropic flow:
- Pressures, temperatures and Velocities at the throat and test Section.
 - Area of cross-section of the test section
 - Mass flow rate
 - Power required for driving the compressor.

Or

- (b) Derive the energy equations : $a^2 / \gamma - 1 + \frac{1}{2}c^2 = \frac{1}{2}c_{\max}^2 = a_0^2 / \gamma - 1 = h_0$. Stating the assumptions used.

12. (a) Air enters a long circular duct ($d = 12.5$ cm, $\bar{f} = 0.0045$) at a Mach number 0.5, pressure 3.0 bar and temperature 312 K. If the flow is Fanno flow throughout the duct determine:
- The length of the duct required to change the Mach number to 0.7
 - Pressure and temperature of air at $M = 0.7$
 - The length of the duct required to attain limiting Mach number
 - State of air at the limiting Mach number.

Or

- (b) The conditions of a gas in a combustor at entry: $P_1 = 0.343$ bar, $T_1 = 310$ K, $C_1 = 60$ m/s. Determine the Mach number, pressure, temperature and velocity at the exit if the increase in stagnation enthalpy of the gas between entry and exit is 1172.5 kJ/kg. Take $c_p = 1.005$ kJ/kg-K, $\gamma = 1.4$.

13. (a) A normal shock occurs in the diverging section of a convergent-divergent air nozzle. The throat area is 1/3 of exit area and the static pressure at exit is 0.4 times of stagnation pressure at the entry. The flow is throughout isentropic except through shock. Determine:
- The Mach numbers M_x and M_y
 - The static pressure
 - The area of cross-section of the nozzle at the section of the nozzle where the normal shock occurs.

Or

- (b) Starting from the energy equation for flow through a normal shock obtain the following relations:
- (i) $C_x C_y = a^{*2}$
 - (ii) $M^*_x M^*_y = 1$.
14. (a) An aircraft flies at 960 kmph. One of its turbojet engines takes in 40 kg/s of air and expands the gases to the ambient pressure. The air-fuel ratio is 50 and the lower calorific value of the fuel is 43 MJ/kg. For maximum thrust power determine:
- (i) Jet velocity
 - (ii) Thrust
 - (iii) Specific thrust
 - (iv) Thrust power
 - (v) Propulsive, thermal and overall efficiencies and
 - (vi) TSFC.

Or

- (b) Explain with neat sketches the principle of operation of:
- (i) Turbo fan engine and
 - (ii) Ram jet engine.
15. (a) Explain with a neat sketch the working of a turbo-pump feed system used in a liquid propellant rocket.

Or

- (b) A rocket flies at 10,080 kmph with an effective exhaust jet velocity of 1400 m/s and propellant flow rate of 5.0 kg/s. If the heat of reaction of the propellants is 6500 kJ/kg of the propellant mixture, determine:
- (i) propulsion efficiency and propulsion power
 - (ii) engine output and thermal efficiency
 - (iii) overall efficiency.
-