



Engien Type	4 Stroke
Displacement	177.4 CC
Cylinder	Arrngement Single
Maximum Power	12.52 KW @ 8500 RPM
Maximum Torque	15.5 NM @ 6500 RPM
Bore x Stroke	62.5 mm x 57.8mm
Compretion Ratio	9.5:1
Carburettor Mikuni	BS-29
Valve Train	2 Valve, Single Overhead Cam
Valves per Cylinder	2 Valves
Power to Weight ration	124.08 BHP / TON
Starting	Electric and Kick Start
Idle Speed	1400 RPM
Ignition	IDI-DualMode Digital Ignition
Maximum Speed	124Kmph
Suspension Front	Telescopic Forks 105mm

Suspension Rear	Stoke mono tube inverted Gas Filled Shox [MIG] with Spring Aid
Height	1100 mm
Leght	2085 mm
Width	730 mm
Wheelbase	1320 mm
ground Clearance	180 mm
Saddle Height	790 mm
Rim size Front	1.85 x 17"
Rim Size Rear	1.15 x 17"
Tyre Size Front	90 / 90 x 17" Tubless
Tyre Size Rear	110 x 80 X 17 " Tubless
Brakes Front	270 mm Petal Disc
Brakes Rear	200 mm Petal Disc
Brake Fluid	DOT 3
Kurb Weight	137 Kg
Max. Payload	130 Kg
Full Ccapacity	16 Lts
Reserve	2.5 Lts
Chasis Type	Double Cradle Syncro Stiff
Battery	12 V, 9.0 Ah
Head Lamp	35 / 35 W halogen Hs1, Clear Lens with Multi face reflector
Tail Lamps	0,5 W LED-Twin Triangle with Prism.